

R200 SWINGARM

HIGH-PERFORMANCE, RUGGED TIRE CHANGER
FOR HIGH VOLUME SHOP USE

VERSATILE SWINGARM DESIGN
**SELF-CENTERING RIM CLAMPS OFFER A WIDE
VARIETY OF WHEEL AND TIRE COMBINATIONS**

- Pedal-operated tire inflation with pressure gauge
- Tabletop air blast inflation for quick tire bead seating on difficult tires.
- Large 6.9 gallon air tank located inside column frees space behind machine

**EXTRA LARGE FRAME
AND ARM DESIGN
HANDLES LARGER
TIRE DIAMETERS
UP TO 52"**



**SHOWN: Lifting roller
demounting lower bead**

PNEUMATIC TOP BEAD TOOL & LIFTING ROLLER

- Standard equipment includes a lower bead lifting roller and top bead pressing tool for larger and specialty tires



STANDARD PLASTIC MOUNTING / DEMOUNTING HEAD

- Improved design style
- Durable composite for long life



220V VARIABLE SPEED CONTROL INVERTER

- Exclusive motor inverter controls and regulates rotational speed
- Slows as the stress on the bead increases avoiding damage to the tire
- Available 110V high torque single speed drive model



**INCLUDES
STORAGE
CABINET**

TECH-FRIENDLY DOUBLE- ACTING SIDE BEAD BREAKER

- Extra wide tool shaft allows operation for tires up to a 18" maximum width
- POWER IN, PARK, and POWER OUT works on low-profile, large steel or alloy rims

ROTARY[®]

BY ROTARY SOLUTIONS

R200 SWINGARM TIRE CHANGER

FEATURES

- 220v variable speed drive supplies needed torque with the ability to regulate speed to reduce tire stress and damage
- Available 110V high torque single speed drive model
- Hand controlled bead breaker
- Valve tray
- Column-mounted storage case
- Tire paste lubricant and brush

R200 services:



Optional equipment may be required

SPECIFICATIONS:

External clamping	10" - 26"
Maximum torque to chuck	885 Ft/L bs (1200 Nm)
Internal clamping	12" - 28.5"
Max. tire diameter	52"
Max. tire width	16"
Max. bead breaker opening	2" - 18"
Bead breaker cylinder power at 145 psi	6,745 Ft/L lbs
Power supply	2 HP / 220v / 1Ø / 60 Hz VARIABLE SPEED OR 110v / 1Ø / 60 Hz SINGLE SPEED

Site Requirements: 110V / 115-145 psi air supply

ROTARY WHEEL SERVICE EQUIPMENT carries a 3 year parts warranty and 1 year labor warranty. See website for details.

STANDARD EQUIPMENT



PLASTIC TOOL HEAD VSG800A60 Tool head with support



VSG800A117KIT Tool protection kit for metal mount / demount head (2 x kit)



VSG800A11 Bead breaker protection Qty. of 1

VSG800A11K / Qty. of 5



VSG800A6KIT Clamp Protectors / 24" - 26" (4 pcs)

OPTIONAL ACCESSORIES



VSG800A107 FAST FIT MOTORCYCLE ADAPTERS
+ 5" from outside



SMALL WHEEL ADAPTER VSG800A111KIT
Reduces clamping capacity to 8" for ATVs and lawn equipment tires.
- requires VSG800A107 wheel clamps



ROTARY SOLUTIONS

To learn more about all of our automotive service and repair solutions or to contact your local distributor, visit us at www.RotarySolutions.com today.

Need assistance or have questions? We're here to help:
800.445.5438 / Sales: insidesales@rotarysolutions.com
Technical Support: WS-techsupport@rotarysolutions.com

ROTARY SOLUTIONS™

2700 Lanier Drive | Madison, IN 47250, U.S.A.

Lit# Rotary.R200.Cutsheet.05.01.2026

©2026 VEHICLE SERVICE GROUP™
All Rights Reserved. Unless otherwise indicated, ROTARY SOLUTIONS™, VEHICLE SERVICE GROUP™, DOVER® and all other trademarks are property of Dover Corporation and its affiliates.

Product specifications, part numbers, images and component descriptions are subject to change without notice or liability.