

LIFT PRODUCT ACCESSORIES

MOBILE TIRE AND WHEEL LIFTS

Reduce the risk of shoulder and back injuries and limit potential worker's comp claims.

Air operated wheel lifts can remove and position any size wheel or tire weighing up to 500 pounds, making it much easier and more ergonomic for technicians to work on heavy-duty trucks, buses and construction equipment.



WATCH AND
LEARN ABOUT
TIRE LIFTS

MW200

200 LBS. CAPACITY LIFT AT 100PSI

FEATURES:

- Offset column for easy transfer to balancer
- Single lever control
- Valves to adjust speed
- Includes air hose and auxiliary air connection
- Easy to maneuver 5" locking casters
- Tray for parts and lug nuts
- Extra strong US steel construction

MW500

500 LBS. CAPACITY LIFT AT 100PSI

FEATURES:

- Redundant lifting cables inside column for added safety
- Back stop allows 5" of adjustable height
- Split tire rollers on bottom arms for dually tires
- Air tool connection reduces hoses in shop
- Includes pressure regulator to prevent overloading
- Tray for parts and lug nuts
- Includes tie-down strap
- Extra strong US steel construction

MODEL	#MW200 #MW500
Lift Capacity	200 lbs. 500 lbs.
Weight	135 lbs. 336 lbs.
Height	61 1/2" 72"
Width	30 1/2" 42"
Length	30" 47 1/2"
Tires Size	20" to 30" APPROXIMATE 30" to 45" APPROXIMATE
Stroke	40"
Operating Pressure	100 psi
Time of Full Rise	6 seconds

Units come in blue only - some assembly required.



ROTARY SOLUTIONS

To learn more about all of our automotive service and repair solutions or to contact your local distributor, visit us at www.RotarySolutions.com today.

Need assistance or have questions? We're here to help: 800.445.5438

Sales: insidesales@rotarysolutions.com / Technical Support: LD-techsupport@rotarysolutions.com

ROTARY SOLUTIONS™

2700 Lanier Drive | Madison, IN 47250, U.S.A.

Lit# [Rotary MW200.MW500 Cutsheet.01.10.2025](#)

©2025 VEHICLE SERVICE GROUP™
All Rights Reserved. Unless otherwise indicated, ROTARY SOLUTIONS™, VEHICLE SERVICE GROUP™, DOVER® and all other trademarks are property of Dover Corporation and its affiliates.

Product specifications, part numbers, images and component descriptions are subject to change without notice or liability.