

R180 PRO

3D AUTO TECHNOLOGY


WHEEL DIMENSION SONOR AND LASER RIM SCANNER TECHNOLOGY FINDS EVERY MEASUREMENT NEEDED FOR PERFECT BALANCING

TRUE AUTOMODE

The sonar hood automatically detects wheel dimension when the cover is lowered











Automatic stop in the internal unbalanced position.

AUTOMATIC LOCK- IN POSITIONING ELIMINATES THE NEED TO FIND WEIGHT **POSITIONS MANUALLY**



The functions related to each key vary by use and are identified by icons on the display for easier understanding.

EASY INTERACTIVE **OPERATION WITH GUIDED BALANCING FUNCTIONS**

- Prompts guide techns through every step and procedure
- Programs feature:
- automatic system storage for distance and diameter measurements
- hidden weight and split program for spoked wheels
- 3 automatic ALU S programs

AUTOMATIC BALANCING MODE SAVES TIME AND MATERIALS

Faster efficient balancing reduces spins and wheel weight consumption.





LASER WHEEL SCANNER INDICATES **EXACT POSITIONING FOR WEIGHTS**

- Laser scans rim profile and balancing program is auto selected
- · Wheel spoke quantities are checked
- · Position of hidden weights is located
- · Adhesive weights are positioned and memorized
- · Easily switch readout from ounces to grams


ROTARY'S FASTEST AND MOST PRECISE AUTOMATIC WHEEL BALANCER



LINKED MONITOR KEYPAD

• Linked directly to a standard 19" monitor







WATCH & LEARN!

Scan code to watch product videos.



ROTARY

R180 PRO 3D AUTO PASSENGER WHEEL BALANCER

FEATURES

- Passenger, Light Truck adapters standard
- 8-piece collet set included
- · Large display for easy operation
- 12 programmed features for car, light trucks, and motorcycle wheels

R180 PRO services:



Optional equipment may be required

SPECIFICATIONS:

Rim diameter	10" - 30"
Rim width	1.5" - 22"
Maximum tire diameter	44"
Max. assembly weight	176 lbs.
Read out accuracy	1g
Cycle time	6 seconds
Rotation speed (RPM)	< 100
Power supply	110v / 1Ø / 60 Hz

DIMENSIONS:

HEIGHT: 57.125" / 66.5" with hood up

WIDTH: 53.625"

DEPTH: 30.375" / 36.625" with hood up

ROTARY WHEEL SERVICE EQUIPMENT carries a 3 year warranty. See website for details.

STANDARD ACCESSORIES



GAR 112 Light truck cone 3.75"-5" (95-124mm)

VS129591100 **Eight-piece** double-sided Collet Kit 2.21"- 4.36" (56-110.7mm)

- Clad Wheel Problem Solver
- Static Imbalance Solution
- Lower Taper = Better Mounting
- No Wheel Hub Interference



Large quick nut replacement lock



OPTIONAL ACCESSORIES



GAR 113 Light truck cone 4.65"-6.8" (118-174mm)




GAR124 Spacer May be used with GAR112 and the #8,9,10,11 collets



2.07"- 4.76" (52.5mm-122mm)

- · Clad Wheel Problem Solver
- Includes collets #1 thru #9
- Static imbalance solution
- Lower taper = better mounting surface with no wheel hub interference





HW200299409

North American Flange Plate Kit 40mm



GAR324 Wheel lift

- Automatic compensation of wheel weight
- Memorizes wheel weight - when wheel is removed, there are no forces on balancer shaft.



ROTARY SOLUTIONS

To learn more about all of our automotive service and repair solutions or to contact your local distributor, visit us at www.RotarySolutions.com today.

Need assistance or have questions? We're here to help:

800.445.5438 / Sales: insidesales@rotarysolutions.com Technical Support: WS-techsupport@rotarysolutions.com

ROTARY SOLUTIONS™

2700 Lanier Drive | Madison, IN 47250, U.S.A.

Lit# Rotary.R180 PRO.Cutsheet.05.01.2025

©2026 VEHICLE SERVICE GROUP™ All Rights Reserved. Unless otherwise indicated, ROTARY SOLUTIONS™, VEHICLE SERVICE GROUP™, DOVER® and all other trademarks are property of Dover Corporation and its affiliates.

Product specifications, part numbers, images and component descriptions are subject to change without notice or liability.