

R146RP SWINGARM PRO

HIGH-PERFORMANCE, EXTRA
HEIGHT SPEEDCHANGER

**HEAVY DUTY SWING ARM
STRUCTURE FOR HIGH
VOLUME SHOP USE**

- Exclusive 110v single speed motor provides needed torque
- Self-centering chuck with a wide clamping range to handle a variety of needs.



SHOWN: Helper arm demounting lower bead

STANDARD WITH AIR-DRIVEN PLUS91SA HELPER ARM*

- For large and special tires
- Includes a lower bead lifting roller and pneumatic top bead pressing tool



HAND CONTROLLED SIDE BEAD BREAKER

- Double-acting bead breaker cylinder is designed to work on low-profile and large steel or alloy rims.
- Extra wide tool shaft allows operation on tires up to 15" maximum tire width.



ROBUST CENTER FRAME

- Extra large 46" frame allows for a maximum tire diameter of 46"
- Arm design for high performance, high volume use



ENCAPSULATED AIR TANK

- Built inside the changer column to free up space behind the machine.



**WATCH
& LEARN!**

Scan code to watch
product videos.



REMOVABLE PEDAL ASSEMBLY

- Allows for easy access maintenance

*NOTE: PLUS91SA IS NOT INSTALLED PRIOR TO DELIVERY

ROTARY
BY ROTARY SOLUTIONS

R146RP
SWINGARM TIRE CHANGER

FEATURES

- 110v drive motor supplies needed torque
- Gear box is supported by steel plates to avoid flex
- Valve tray
- Tire paste lubricant and brush

R146RP services:



Optional equipment may be required

SPECIFICATIONS:

External clamping	10" - 26"
Maximum torque to chuck	885 Ft/Lbs (1200 Nm)
Internal clamping	12" - 28.5"
Max. tire diameter	45" (1143 mm)
Max. tire width	15" (380 mm)
Max. bead breaker opening	15" (380 mm)
Bead breaker cylinder power at 145 psi	6,745 Ft/Lbs (3060 kg)
Power supply	110v / 1Ø / 60 Hz

Site Requirements: 110V / 115-145 psi air supply

ROTARY WHEEL SERVICE EQUIPMENT carries a 3 year warranty.
See website for details.

STANDARD EQUIPMENT



PLASTIC TOOL HEAD
VSG800A60 Tool head with support



VSG800A117KIT Tool protection kit
for metal mount / demount head (2 x kit)




VSG800A11
Bead breaker protection
Qty. of 1
VSG800A11K / Qty. of 5



VSG800A6KIT
Clamp Protectors / 24" - 26" (4 pcs)

OPTIONAL ACCESSORIES



VSG800A107
FAST FIT MOTORCYCLE
ADAPTERS
+ 5" from outside



SMALL WHEEL
ADAPTER VSG800A111KIT
Reduces clamping capacity to 8" for
ATVs and lawn equipment tires.
- requires VSG800A107 wheel clamps



ROTARY SOLUTIONS

To learn more about all of our automotive service and repair solutions or to contact your local distributor, visit us at www.RotarySolutions.com today.

Need assistance or have questions? We're here to help:
800.445.5438 / Sales: insidesales@rotarysolutions.com
Technical Support: WS-techsupport@rotarysolutions.com

ROTARY SOLUTIONS™
2700 Lanier Drive | Madison, IN 47250, U.S.A.

Lit# Rotary.R146RP.Cutsheet.10.01.2024

©2024 VEHICLE SERVICE GROUP™
All Rights Reserved. Unless otherwise indicated, ROTARY SOLUTIONS™,
VEHICLE SERVICE GROUP™, DOVER® and all other trademarks are
property of Dover Corporation and its affiliates.
Product specifications, part numbers, images and component
descriptions are subject to change without notice or liability.