

DP18PR0

HEAVY DUTY TWO POST LIFT 18,000 lbs. Capacity



FEATURES:

Symmetrical column design

3-stage front and rear arms to service a wider range of vehicles

Three height configuration models for most ceiling heights

Top mounted direct pull technology

- · Cylinder rod concealed inside carriage
- · Overhead cable equalization
- Single point lock release
- Spring operated arm restraints
- · Includes adapter storage
- Durable powder-coated finish
- · ALI certified

DP18PN000BL / RD

DP18PN001BL / RD

DP18PN002BL / RD

Rise with 10" Adapter

Height to Shut-Off

Overall Width

Drive-Thru

Inside Columns

Voltage/Amps

Motor/Phase

Arm Reach (Min/Max)

DP18PN000BL / RD DP18PN001BL / RD

DP18PN002BL / RD

Minimum Adapter Height

Capacity

Extension

INCLUDES THREADED TRUCK ADAPTERS AND (4 each) 5" and **10" ADAPTER EXTENSIONS**

12' 10 3/4" Low Ceiling

14' 7" Standard Height

16' 7" Extended Height

147 1/4" Low Ceiling

208V - 230V, 17 amps

12' 11 3/4" Low Ceiling

14' 8" Standard Height

16' 8" Extended Height

167 1/4" Standard Height 191 1/4" Extended Height

18,000 lbs.

12' 10 3/8"

119 5/8"

108 1/4"

30"/61"

2HP / 1Ph

5 1/2"

83 1/4"

HEAVY DUTY 3-STAGE ARM DESIGN

The DP18 Pro's industry leading 30" minimum arm reach creates the needed clearance to swing arms between tires of shorter wheelbase vehicles.

- 3-stage arms extend and retract from 61" to 30"
- 5 1/2" minimum adapter height from floor



FWD DP18PN002BL

Extended Height Lift



ALI GOLD CERTIFIED

Forward Lift DP10A meets the highest industry safety and performance standards. Your assurance of certification is the gold ALI/ETL certified label.



996 Industrial Drive Madison, IN 47250

Fax: 812.273.7329









Unless otherwise indicated, Forward Lift, Vehicle Service Group®, Dover and all other trademarks are property of Dover Corporation and its affiliates,

Phone: 800.423.1722

MINIMUM REQUIRED CEILING HEIGHT